





## + Features

 EN:795:2012 – Type B  
 ANSI/ASSE Z359.18-2017 Type D

- 1** Overhead fall protection system that protect users from falls during work at heights (Fall factor 0).
- 2** **Manual installation without the need for a crane** thanks to its light weight: 19 kg.
- 3** Installed into a housing tube previously inserted into the concrete structure (column/wall).
- 4** Provides a smooth 360° rotation, covering a safe working area of up to approximately 125m<sup>2</sup>.
- 5** Built-in energy-absorbing device that reduces the impact forces transferred to the user and to the structure in the event of a fall.
- 6** Easy, intuitive installation. Cost effective: no crane need.
- 7** Protect users from falls from heights, specially during the structure building phase: positioning of panels, perimeter protection and stairwells, etc.
- 8** Up to 2 users connected at the same time.

## + Elements

 **Manual installation**

 **x2 Users allowed**



**Alupercha**  
Main anchor point.



**Housing tube.**  
Element to house the Alupercha. CE marking.



**Leveler.**  
Ensures the CE housing tube is vertical.




**Hook.**  
To bring the next Alupercha closer.



**Retractable device.**  
Device that locks the descent in the event of a fall.



**Harness.**  
PPE that must be worn by the user.



**Sling.**  
Optional, if the Alupercha is handled using a crane.